



#### Features & Benefits

- Portable sampling system for quantifying solids production in, primarily, oil process streams.
- Open system when operated.
- Standard connection to the SFU is ¼" NPT female. Adaptors can be supplied for alternative connections.
- Filter thimbles are available as standard with mesh sizes of; 3, 5, 30, 50, and 150µ.
- Other mesh sizes can be supplied on request.
- A pressure relief valve provides protection against over pressure from filter blockage.
- 100 PSI gauge has a protection device against over pressurisation.

Type		Documentation & Design	
Part Number	850341	Code	Classified as SEP under European Directive 97/23/EC
M.A.W.P.	Open system with 6.9 Bar(g) (100 psi(g)) pressure indication	Service	All wetted parts are stainless steel
Material	AISI 316	Standard	Hydrostatic test Certificate Leak test Report
Net Weight	3.9kg (8.6lb) Boxed 8.6kg (19lb)		
Dimensions	H x W x L 165mm x 350mm x 460mm (6.5" x 14" x 18")		

### ingenious simplicity

Proserv UK Ltd.  
 4 Greenbank Place  
 East Tullos Industrial Estate  
 Aberdeen AB12 3BT.  
 info@proserv.com [www.proserv.com](http://www.proserv.com)

**proserv**